

TECHNICAL DATA SHEET

G-2399

ISSUE DATE: 03/11/10

PRODUCT DESCRIPTION	G-2399 is a low viscosity glue lap adhesive used when good wet tack and quick bond are essential.	
USES	Michelman coated paper or cardboard; uncoated paper.	
FEATURES	<ul style="list-style-type: none">• Adhesion to Michelman coated paper or cardboard.• High wet tack.• Quick bond.• Machines well.• Cost effective.	
TECHNICAL PROPERTIES	Viscosity	1000 ± 200 cPs
	Solids	54 ± 1%
	pH	4.0 - 5.0
	Specific gravity	1.08 g/cc
PRODUCT APPLICATION	Recommended for extrusion applicators.	
ADDITIONAL DATA	N/A.	
PACK SIZES	Drum, tote, bulk.	
STORAGE CONDITIONS	Keep from freezing.	
LIMITATIONS	Six months in the original unopened container when stored in a cool, dry area.	

Any recommendations contained herein or any information given by any Dural representative is based on tests and information believed to be accurate. However, since we have no control over the conditions under which our products are transported, stored, handled, or used by purchasers, all recommendations and sales are made on condition that Dural will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. It is the user's responsibility to ensure that this sheet is current prior to using the product.