

TECHNICAL DATA SHEET

G-3059

ISSUE DATE: 05/03/2016

PRODUCT DESCRIPTION G-3059 is a compounded crosslinkable polyvinyl acetate emulsion adhesive. It has very good wet tack. It will resist high humidity conditions and 24 hours cold water soaks.

USES Paper lamination (Gaylord production); bulk boxes lamination; glue lap and splicing.

FEATURES

- Meets or exceeds Rule 41
- Optimal crush resistance and excellent green strength
- Good machinability
- Adheres well on various paper stocks
- Meet requirements of FDA Regulation: 21 CFR 175.105: indirect food adhesive

TYPICAL PROPERTIES

Viscosity (cps):	1,800 - 2,000
Solids (%):	49.0 - 51.0
Specific Gravity:	1.11
pH:	3.0 - 4.0

PRODUCT APPLICATION Roll coater; extruder; wheel.

ADDITIONAL DATA

VOC Content (g/l): 19	Min. Operating Temp.: 10°C
Freeze Thaw Stability: Stable	Application Temp.: 15° - 30°C
Color: Wet - White, Dry - Clear	

PACK SIZES

220 kg drum	
1,100 kg tote	Weights may vary

STORAGE CONDITIONS Keep from freezing. Keep away from direct sunlight or heat.

LIMITATIONS Shelf Life: Six (6) months when stored as recommended.

Any recommendations contained herein or any information given by any Dural representative is based on tests and information believed to be accurate. However, since we have no control over the conditions under which our products are transported, stored, handled, or used by purchasers, all recommendations and sales are made on condition that Dural will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. It is the user's responsibility to ensure that this sheet is current prior to using the product.